

TECHNICAL DATA SHEET

DLC12-55EV

Applications



CYCLIC




STATIONARY



SOLAR




MARINE



Application

- › Renewable Energy Storage
- › Solar/wind generating storage cyclic
- › Hybrid Energy Power Storage
- › New Energy Vehicle
- › Hybrid Electric Vehicle
- › Backup power supply
- › Other Standby, Cyclic Power Systems



Specification

Nominal Voltage	12V
Nominal Capacity	62Ah
Design life	12 years
Terminal	M6 Terminals
Approx. Weight	Approx 17.00 kg
Container Material	ABS
Rated Capacity	55.5Ah 10Hour Rate (5.55A to 10.8V)
	48.5Ah 5Hour Rate (9.70A to 10.5V)
	35.4Ah 1Hour Rate (35.4A to 9.6V)
Internal resistance	Full charged at 25 °C: 6.0 Ohm
Max. Discharge Current	800.0A(5S)
Operating Temperature	Discharge: -40 ~60 °C (-40~ 140 °F)
	Charge: -20 ~50 °C (-4~ 122 °F)
	Storage: -20 ~50 °C (-4~ 122 °F)
Charge Method (25 °C)	Charge current: Max.30.0A ; Recom.5.5~11A
	Float Charge voltage(-3mV/°C) : 13.7-13.9V, recom. 13.7V(Full floating system)
	Cycle charge: 14.7-15.0V, recom. 14.7V(-5mV/°C)
	3% of capacity declined per month at 20 °C
Unit: mm Dimension: 229(L)×138(W)×208(H)×212(TH)	



TECHNICAL DATA SHEET

DLC12-55EV

Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	144.9	109.9	88.5	53.8	40.3	35.4	23.3	16.3	10.2	6.8	6.04	3.23
1.67V	142.3	107.9	87	52.8	39.6	34.7	22.8	16	10.1	6.6	5.92	3.17
1.70V	139.7	105.9	85.3	51.8	38.8	34.1	22.4	15.7	9.9	6.5	5.8	3.11
1.75V	137	103.9	83.7	50.8	38.1	33.5	22	15.4	9.7	6.4	5.73	3.05
1.80V	131.8	99.9	80.5	48.8	36.6	32.2	21.1	14.8	9.3	6.2	5.55	3.02


Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	279	211.6	170.4	103.5	77.6	68	44.7	31.4	19.8	13	11.65	6.31
1.67V	274	207.7	167.3	101.6	76.1	66.8	43.9	30.8	19.4	12.8	11.41	6.17
1.70V	268.8	203.9	164.2	99.7	74.7	65.5	43.1	30.2	19	12.6	11.22	6.13
1.75V	263.8	200.1	161.1	97.8	73.3	64.3	42.3	29.6	18.7	12.3	10.98	6.04
1.80V	253.6	192.4	154.9	94	70.5	61.8	40.7	28.5	18	11.8	10.55	5.98


TECHNICAL DATA SHEET

DLC12-55EV


Curves of discharge capacity and ambient temperature




Curves of charging characteristics




Discharge characteristics at different discharge rate(20°C)



Curves of cycle life



Curves of self-discharge and storage time



Curves of float voltage and ambient temperature

